

Description

Clear, powerful lubricant with anti-fling properties. A clear, polymer based lubricant ideal for use on chains and sprockets, pins and bushes where its anti-fling performance is important and where a clear invisible film is necessary for cosmetic reasons. It penetrates into the chain, depositing a film of extreme pressure additives and polymers which will withstand pressure washing.

Benefits & Features

- Clear polymer based product
- Fortified with PTFE for improved load resistance
- Good thermal stability
- Extreme pressure additives
- Will not fling off
- Extends chain life
- Resists and prevents corrosion
- Clean to use
- Penetrates deeply
- Withstands pressure cleaning

Directions for Use

Shake can well. Spray onto surface from 10-20cm, allow a few seconds for the solvent to disperse and re-start machinery.

Technical Data

Appearance:	Slightly amber high pressure spray drying to a thick sticky stringy polymer film
Odour:	Oily solvent
Contents:	Blend of refined mineral oils, tackifier, extreme pressure additives, polyisobutylenes, PTFE and hydrocarbon propellants. No silicones or chlorinated solvents
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	-50° to 150°C continuous, 300°C intermittent
Relative Density:	0.780
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

