

Description

PROTEAN Hydraulic VHVI 68 is a food grade, non-toxic, developed for hydraulic systems used in food, drink and pharmaceutical processing and packaging equipment. Also suitable for other hydraulic systems where a clean, non-staining hydraulic oil is desired.

Benefits & Features

- Low coefficient of friction provides excellent lubrication and reduces wear
- Semi synthetic oil provides extremely wide temperature stability and ensures greatly extended servicing intervals
- Low foaming reduces residue and scum build-up, which extends maintenance intervals

Directions for Use

PROTEAN Hydraulic VHVI 68 is suitable for hydraulic systems designed to operate in applications where ISO 68 oil viscosity grade has been specified. Follow manufacturer's instructions. It is important to purge the system of the previous oil prior to recharging with PROTEAN Hydraulic VHVI 68.

Technical Data

| | |
|------------------------------|---|
| Category: | H1 – Lubricants with incidental contact |
| NSF Registration No: | 162768 |
| Allergens: | Does not contain allergens, genetically modified ingredients, nut oil or derivatives. |
| Appearance: | Clear fluid |
| Base Oil: | Blend of synthetic oils |
| Viscosity (ISO 3104): | 68 at 40°C, 9.9 at 100°C |
| Viscosity Index (ISO 2909): | 128 |
| Relative Density: | 0.85 |
| Flash Point (ISO 2592): | 222 |
| Solubility: | Insoluble in water |
| Operating Temperature Range: | -15° to 150°C |
| Pack Sizes: | 20 Ltr (TF9220) 205 Ltr (TF9299) 1000 Ltr (TF9200) |



The content of this data sheet is given in good faith but without warranty.