

Description

IS75 is a premium-grade oil based product that gives powerful, clear lubrication to chains and other moving parts where a dark coloured lubricant would be undesirable. Its anti-fling properties make it important when used on moving parts, penetrating into the mechanism and depositing a film of extreme pressure additives which will withstand pressure washing.

Benefits & Features

- Clear, non-staining
- Extreme pressure additives for heavy use
- Effective on fork lift chains, sprockets, pins and bushes
- Tenacious – will not fling off
- Penetrates deeply
- Withstands pressure washing
- PTFE fortified

Directions for Use

Shake can well. Spray onto mechanism from 10-20cm, allow a few seconds for solvent to flash off and re-start equipment.

Technical Data

Appearance:	Slightly amber
Odour:	Oily solvent
Contents:	Blend of mineral oils, tackifier, solvent, extreme pressure additives, PTFE and hydrocarbon propellants. No silicones or chlorinated solvents
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	-50° to 180°C
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

