TECHNICAL DATA SHEET



WR2 CALCIUM GREASE **TG7204**

Description

Water resistant grease for use in industrial and marine applications. A premium quality, water resistant grease for use in industrial and marine applications where the presence of water and humid atmospheres can effect lubricating performance and be detrimental to the protection of parts from corrosion. TG7204 is suitable for plain and anti-friction bearings.

Benefits & Features

- · High degree of water resistance
- Excellent corrosion protection
- · Good sealing properties

Directions for Use

Apply by standard grease gun or via a central lubrication system capable of pumping NLGI 2 greases.

Technical Data

Appearance: Smooth brown odourless grease

NLGI Classification: 2

Base Oil: Highly refined mineral oil

Base Oil Viscosity: 100cSt @ 40°C

Thickener: Calcium 12 hydroxy stearate

Worked Penetration: 265 to 295

Water Washout: 2@ Relative Density: 0.93

Solubility: Insoluble in water
Dropping Point: 140°C minimum
Temperature Range: -20 to 110°C

Oil Separation: 3% max @40°C for 7 days
Pack Size: 12 x 400g cartridges

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

