

SECTION 1: Identification of the substance/mixture and of the company/undertakin

SAFETY DATA SHEET VEHICLE SANITISER D202

1.1. Product identifier			
Product name:	duct name: DEFENCE+ VS (VEHICLE SANITISER) NEW CAR SECENT		
Product code:	D202		
1.2. Relevant identified uses	of the substance or mixture and uses advised against		
1.3. Details of the supplier of	f the safety data sheet		
Supplier			
TYGRIS Ltd.			
31 Kyle Road, Irvine, K	A12 8LE		
Tel +44 (0) 1294 311 0	66		
Email team101@tygris	industrial.com		
Further information obt	ainable from:		
Technical Department			
1.4. Emergency telephone nu	umber		
Emergency telephone	+44 (0) 1294 311 066		
SECTION 2: Hazards identifi	cation		
2.1. Classification of the sub	stance or mixture		
Classification under CLP: Aqua	atic Chronic 3: H412; Eye Irrit. 2: H319; Flam. Aerosol 1: H222; STOT SE 3: H336; -:		
EUH208; -: H229			
Most important adverse effects	S: Contains limonene. May produce an allergic reaction. Extremely flammable aerosol. Pressurised container: May burst if heated. Causes serious eye irritation. May cause drowsiness or dizziness. Harmful to aquatic life with long lasting effects.		

2.2. Label elements

Label elements:

Hazard statements:

EUH208: Contains limonene. May produce an allergic reaction. H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

H319: Causes serious eye irritation.

H336: May cause drowsiness or dizziness.

H412: Harmful to aquatic life with long lasting effects.

Hazard pictograms:

GHS02: Flame



GHS07: Exclamation mark

Signal words: Danger Precautionary statements:

P102: Keep out of reach of children.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.







P211: Do not spray on an open flame or other ignition source.

P251: Do not pierce or burn, even after use.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

SECTION 3: Composition/information on ingredients

PETROLEUM GASES, LIQUEFIED

EINECS	CAS	PBT / WEL	CLP Classification	Percent
270-704-2	68476-85-7	Substance with a Community workplace exposure limit.	Flam. Gas 1: H220; Press. Gas: H280	30-50%
ETHANOL				
200-578-6	64-17-5	Substance with a Community workplace exposure limit.	Flam. Liq. 2: H225	30-50%
PROPAN-2-OL				
200-661-7	67-63-0	-	Flam. Liq. 2: H225; Eye Irrit. 2: H319; STOT SE 3: H336	10-30%
METHANOL				
200-659-6	67-56-1	-	- Flam. Liq. 2: H225; Acute Tox. 3: H331; Acute Tox. 3: H311; Acute Tox. 3: H301; STOT SE 1: H370	<1%
LINALOOL				
201-134-4	78-70-6	-	Skin Sens. 1B: H317	<1%
DIDECYLDIMET	THYLAMMONIUMCH	ILORIDE		
230-525-2	7173-51-5	-	Skin Corr. 1B: H314; Aquatic Acute 1: H400; Acute Tox. 4: H302	<1%

<u>Description of first aid measures</u>

Skin contact:	Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash immediately with plenty of soap and water.
Eye contact:	Bathe the eye with running water for 15 minutes. Consult a doctor.
Ingestion:	Wash out mouth with water. Consult a doctor.





SAFETY DATA SHEET VEHICLE SANITISER D202

	Inhalation:		e casualty from exposure ensuring one's own safety whilst doing so. Consult a
			Move the exposed person to fresh air.
<u>4.2. Most important sy</u>	-		-
	Skin contact:		may be irritation and redness at the site of contact.
	Eye contact:		may be irritation and redness. The eyes may water profusely.
	Ingestion:		may be soreness and redness of the mouth and throat.
	Inhalation:		may be irritation of the throat with a feeling of tightness in the chest. Exposure use coughing or wheezing.
	Delayed / imme	diate effe	cts: Immediate effects can be expected after short-term exposure.
4.3. Indication of any in	mmediate medical	attentio	n and special treatment needed
	Immediate / spe	cial treat	ment: Eye bathing equipment should be available on the premises.
SECTION 5: Firefight	ing measures		
5.1. Extinguishing med	dia		
	Extinguishing m	edia:	Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.
5.2. Special hazards a	-		
	-	ds: In cor	nbustion emits toxic fumes.
5.3. Advice for fire-figh			
	Advice for fire-fig	ghters:	Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.
SECTION 6: Accident	tal release measur	es	
6.1. Personal precaution	ons, protective eq	uipment	and emergency procedures
	Personal precau	itions:	Refer to section 8 of SDS for personal protection details. If outside do not approach from downwind. If outside keep bystanders upwind and away from danger point. Mark out the contaminated area with signs and prevent access to unauthorised personnel. Turn leaking containers leak-side up to prevent the escape of liquid.
6.2. Environmental pre	ecautions		
	Environmental p	recautior	ns: Do not discharge into drains or rivers. Contain the spillage using bunding.
6.3. Methods and mate	erial for containme	nt and c	leaning up
	Clean-up procee	dures:	Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.
6.4. Reference to other	<u>r sections</u>		
	Reference to oth	ner sectio	ns: Refer to section 8 of SDS.
SECTION 7: Handling	g and storage		
7.1. Precautions for sa	fe handling		
	Handling require	ements:	Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.
7.2. Conditions for saf	e storage, includir	ng any in	compatibilities
	Storage condition	ons:	Store in a cool, well ventilated area. Keep container tightly closed.
	Suitable packag	ing:	Must only be kept in original packaging.
	Tel: +44 (0) 1294 3	ine KA12 8LE 311 066 Version 1 industrial.com Page 3 of 7

Version 1 Page 3 of 7

DEFENCE+

SAFETY DATA SHEET VEHICLE SANITISER D202

7.3. Specific end use(s)

Specific end use(s): No data available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

PETROLEUM GASES, LIQUEFIED

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
UK	1,750mg/m3	2,180mg/m3	-	-
ETHANOL				
UK	1920 mg/m3	-	-	•
PROPAN-2-0	L			
UK	999 mg/m3	1250 mg/m3	-	-
METHANOL				
UK	266 mg/m3	333 mg/m3	-	-

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures:	Ensure there is sufficient ventilation of the area.
Respiratory protection:	Self-contained breathing apparatus must be available in case of emergency.
Hand protection:	Protective gloves. Chemically resistant gloves.
Eye protection:	Safety glasses. Ensure eye bath is to hand.
Skin protection:	Protective clothing.
Environmental:	Not applicable.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State:	Aerosol
Colour:	Colourless
Odour:	Characteristic odour
Flash point°C:	<23

9.2. Other information

Other information: No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.







10.3. Possibility of hazardous reactions

Hazardous reactions:

Hazardous reactions will not occur under normal transport or storage conditions. Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid:

Heat.

10.5. Incompatible materials

Materials to avoid:

Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

SECTION 11: Toxicological information

Haz. decomp. products: In combustion emits toxic fumes.

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MJS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

PROPAN-2-OL

IVN	RAT	LD50	1088	mg/kg
ORL	MJS	LD50	3600	mg/kg
ORL	RAT	LD50	5045	mg/kg
SCU	MUS	LDLO	6	

METHANOL

IVN	RAT	LD50	2131	mg/kg
ORL	MJS	LD50	7300	mg/kg
ORL	RAT	LD50	5628	mg/kg

Relevant hazards for product:

Hazard	Route	Basis
Serious eye damage/irritation	OPT	Hazardous: calculated
STOT-single exposure	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact:	There may be irritation and redness at the site of contact.	
Eye contact:	There may be irritation and redness. The eyes may water profusely.	
Ingestion:	There may be soreness and redness of the mouth and throat.	
Inhalation:	There may be irritation of the throat with a feeling of tightness in the chest. Exposure may cause coughing or wheezing.	
Delayed / immediate effects: Immediate effects can be expected after short-term exposure.		
Other information:	Not applicable.	

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity values:

No data available.







12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

12.4. Mobility in soil

Mobility:

Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification:

This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations:

Transfer to a suitable container and arrange for collection by specialised disposal company. Dispose of contents and container according to national regulations.

Recovery operations: Not applicable.

Disposal of packaging: Not applicable.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

SECTION 14: Transport information

14.1. UN number

UN number: UN1950

14.2. UN proper shipping name

14.3. Transport hazard class(es)

14.4. Packing group

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture by the supplier.

Section 16: Other information

Other information:

This safety data sheet is prepared in accordance with Commission Regulation (EU) No 2015/830.

Phrases used in s.2 and s.3: EUH208: Contains limonene. May produce an allergic reaction.





- H220: Extremely flammable gas.
- H222: Extremely flammable aerosol.
- H225: Highly flammable liquid and vapour.
- H229: Pressurised container: May burst if heated.
- H301: Toxic if swallowed.
- H302: Harmful if swallowed.
- H311: Toxic in contact with skin.
- H314: Causes severe skin burns and eye damage.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H319: Causes serious eye irritation.
- H331: Toxic if inhaled.
- H336: May cause drowsiness or dizziness.
- H370: Causes damage to organs.
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.
- H412: Harmful to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product. Please note that due to the on-going change in regulation from CHIP to CLP, any MSDS information supplied by TYGRIS is only considered accurate at the time of its creation. During this time classifications of substances may change. Therefore it is possible that can art work and MSDS information may differ. As such if you have any concerns we recommend you request a new MSDS from us every 6-12 months.

