

Description

IS10 is a heavy duty mould release agent with a 15% silicone content used for the release of larger and more substantial plastic mouldings. Being safe and inoffensive it is useful as a lubricant around the workplace, and is temperature stable to 300°C.

Benefits & Features

- 15% silicone content – for larger mouldings
- Silicone Viscosity 350cst
- Excellent release properties
- Very high surface slip
- Colourless and non-marking
- Odourless and inoffensive
- Effective as a general lubricant
- Heat stable to 300°C

Directions for Use

Ensure surface to be treated is clean and dry. Shake can well before use and spray evenly from 20 to 30cm – do not overspray. Allow 1 to 2 minutes for carrier solvent to evaporate.

Technical Data

Appearance:	Colourless slightly viscous liquid
Odour:	Slightly sweet when solvent has evaporated
Contents:	Blend of silicone polymer with naphtha and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	Up to 200°C (Cont) 250°C (Intermittent)
Relative Density:	0.795
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

