

## Description

IS70 is an effective moisture repellent, formulated to provide an ultra-thin green film for protection from corrosion of moulds and tooling whilst in store.

## Benefits & Features

- Suitable for use on all metals
- De-watering capability
- Protects from oxidation and rusting
- Ultra-fine film does not interfere with precision-fit parts or with gauging and measurement
- Green colour to show treated parts
- Resists creeping into ejector pins
- Moulds off quickly

## Directions for Use

Shake can well before use. Spray an even coating onto surface from 30cm. Do not over-apply. Leave to dry to an even, visible film.

## Technical Data

Appearance:	Dark green viscous liquid drying to a thin green coating
Odour:	Slightly sweet
Contents:	Blend of refined mineral oils, sarcosine and imidazoline surfactants, sulphonate modified hydrocarbon and paraffin waxes in white spirit and naphtha calcium sulfanate, methanol, dye and hydrocarbon propellants
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	Ambient temperatures
Specific Gravity:	0.755
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at <a href="http://tygrisindustrial.com">tygrisindustrial.com</a> )
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



## Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.