

Description

Lubricates and extends the life of chains and wire ropes. A heavy duty, molybdenum disulphide reinforced lubricant which penetrates deeply into drive chains and wire ropes to give long lasting lubrication, preventing corrosion, wear and chain elongation. It gives outstanding performance under extreme load and is resistant to fling off.

Benefits & Features

- Use on chain blocks, drive chains, fork lift chains and wire ropes
- Extreme pressure additives for heavy loads
- Excellent lubrication properties
- Resistant to flinging off
- Penetrates deeply
- Only a thin film is left on the surface for corrosion prevention
- High resistance to wash off

Directions for Use

Shake can well before use. Spray onto surface to be treated from 15-30cm, allow to penetrate and wipe off excess with a cloth. After use, invert can and spray to clear nozzle.

Technical Data

| | |
|--------------------|---|
| Appearance: | Brown foaming spray |
| Odour: | Oily solvent |
| Contents: | Blend of mineral oils, molybdenum disulphide, bitumen, xylene, white spirit, extreme pressure and dewatering additives, solvent and hydrocarbon propellants. No silicones |
| Flash Point: | <0°C |
| Solubility: | Insoluble in water |
| Temperature Range: | -10°C to 180°C |
| Relative Density: | 0.845 |
| Flammability: | Extremely Flammable |
| Health & Safety: | Consult Safety Data Sheet (available at tygrisindustrial.com) |
| Storage: | Below 50°C |
| Pack Size: | 12 x 400ml aerosols |

Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.

