

Description

4-in 1 PTFE reinforced de-watering, anti-rust, penetrating lubricant. A unique spray with superb properties, suitable for many maintenance tasks, the inclusion of PTFE making for excellent penetrating and lubricating properties. Effective de-watering abilities with residual corrosion protection make for an unsurpassed product.

Benefits & Features

- PTFE reinforced for excellent anti-friction capabilities
- Extreme pressure additives
- PTFE is grafted onto wax particles for better substrate adhesion
- High temperature capacity
- De-watering additives
- Effective penetration and release
- Corrosion inhibitors

Directions for Use

Shake can well before use and spray liberally from 15-30cm, using the 4" extension nozzle for difficult-to-reach areas. Wipe off any excess.

Technical Data

Appearance:	Mid amber
Odour:	Slightly sweet solvent
Contents:	Blend of refined mineral oils, extreme pressure additives, sarcosine and imidazoline surfactants, PTFE in white spirit and n-butyl acetate, wax, corrosion inhibitors, and butane/propane propellant
Flash Point:	<0°C
Solubility:	Insoluble in water
Temperature Range:	20°C to 60°C continuous 25°C to 100°C intermittent
Flammability:	Extremely Flammable
Health & Safety:	Consult Safety Data Sheet (available at tygrisindustrial.com)
Storage:	Below 50°C
Pack Size:	12 x 400ml aerosols



Note

This technical data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department.