

Description

PROTEAN Penetrate+ is a food grade multi-purpose penetrating lubricant containing PTFE. It is a light duty non-toxic lubricating, penetrating and de-watering lubricant and is Ideal for use on chains, bearings & slides in food and clean environments.

Benefits & Features

- Temperature range – 35°C to 140°C
- Good anti-wear properties
- Good dewatering properties
- Excellent penetration
- Long life lubricating film with PTFE
- Excellent corrosion protection
- Does not contain: animal derived materials, nut oils or genetically modified ingredients
- All ingredients are FDA listed

Directions for use

PROTEAN Penetrate+ should be SHAKEN THOROUGHLY BEFORE USE. For best results apply to a clean surface.

Technical Data

Category:	H1 – Lubricants with incidental contact
NSF Registration No:	154134
Allergens:	Does not contain allergens, genetically modified ingredients, nut oil or derivatives.
Appearance:	Pale coloured liquid
Base Oil:	Semi-synthetic fluid
Viscosity @ 40°C:	13.5 to 16.5 cSt
Solids:	PTFE
Relative Density:	0.86
Shell 4 Ball (IP 239) (ASTM D2596):	0.5 mm (40kg for 1 hour)
Copper Corrosion Test (IP 112) (ASTM D130):	1b
Flash Point:	>200°C
Solubility:	Insoluble
Operating Temperature Range:	-35°C to 140°C
Storage:	Storage temperature should be controlled to between room temperature to 40°C.
Pack Sizes:	12 x 500ml Trigger Sprays



The content of this data sheet is given in good faith but without warranty.