



SILICONE FG

FOOD PROCESSING SAFE® SILICONE LUBRICANT

SILICONE FG lubricates, protects, waterproofs and restores. A blend of high quality stable silicone oils. The highly versatile, non-corrosive formula lubricates, protects, waterproofs and restores a wide range of parts and equipment. Ensures superior lubrication of plastics and provides excellent separation and release properties.

Highly water-resistant; repels water from glass, ceramics, fabrics and leather. Eliminates squeaking, binding and sticking and protects metals, plastics, rubbers and other surfaces. Excellent release properties

PRODUCT CODES / FILL SIZES

 30248 / 400ml

APPLICATIONS

- Prevents hardening and freezing of rubber seals
- Prevents plastic assemblies from squeaking and binding
- Renovates plastic, rubber and wooden surfaces
- Provides excellent lubrication especially between parts made of dissimilar materials: e.g. metal/plastic, plastic/plastic, metal/rubber
- For use on virtually any part and equipment made of metal, plastic, rubber, nylon or wood
- Protects and lubricates tools, hoists, jacks, locks, latches, switches and controls, zippers, springs and pulleys
- As a release agent in the moulding of plastic and rubber parts

DIRECTIONS

- Spray light, even film on areas requiring lubrication or protection
- Use extension tube for hard-to-reach areas
- Repeat application if necessary
- Harmless to most common used rubbers and plastics (test prior to use)
- Removal: by Ambersil Amberklene FG
- Do not use on energised (live) equipment



Lubricants



360° Spray System for all angle use



NSF Registered:
category H1, no. 138000



Prevention. Not Detection.
Locked in for safety



Halal Certified Product:
AN001183

TECHNICAL DATA (WITHOUT PROPELLANT)

Appearance	Clear, water-white liquid
Specific Gravity @ 20°C	0.7
Distillation Range of Solvents	50 – 70 °C
Flash Point (closed cup)	< 0°C
Vapour Density (vs. air = 1)	> 3
Dry Film Properties	
Flash Point (closed cup)	> 300°C
Pour Point	< -40°C
Temperature Range	-40 to +200°C
Long Term Stability Temperature (in air)	150°C
Surface Tension	21 mN/m
Dielectric Strength	35 kV
Viscosity @ 20°C	11.000 - 14.000 mPa.s
Based upon the present state of our knowledge and information received from our suppliers, evaluation of this product indicates that it is free from nut oils and their derivatives	

MATERIALS COMPATIBILITY

OK	-
CAUTION	-
NOT OK	-

STORAGE & SHELF LIFE

The product may be stored at normal ambient temperatures and has a shelf life of not less than 6 years with correct storage. Aerosols should always be stored below 50°C, away from direct heat and naked flame.

HEALTH AND SAFETY

A separate Safety Data Sheet (SDS) according to EC Regulation 73/404/EEC and 648/2004/EC is available from Ambersil.com or via info.uk@crcind.com

MISREPRESENTATION ACT 1967

TRADE DESCRIPTIONS ACT 1968

The information given in this publication is based on our experience and reports from customers. There are many factors outside our control and knowledge which affect the use and performance of our products and for which reason no warranty is given, express or implied. Users should make their own tests to determine the applicability of such information or the suitability of any products for their own particular purposes. Statements concerning the use of the products described herein are not to be construed as recommending the infringement of any patent and no liability for infringement arising out of any such use is to be assumed.

Version 4.0
Created: July 2019
Updated: June 2021

CRC Industries UK Ltd.
Wylds Road, Bridgwater
Somerset, TA6 4DD
United Kingdom

t +44 (0)1278 727200
f +44 (0)1278 425644
e sales.uk@crcind.com
w www.ambersil.com

Company Registered No. 04910479

VAT No. GB 821 5195 42

